



MiniPod Bluetooth

Stereo streaming speakers

Performance this good combined with the looks to match, make the MiniPod Bluetooth one of the world's finest active monitors and we are sure that it will continue to be an icon in decades to come.

The MiniPod Bluetooth comes supplied with cables, remote control and Sputnik spikes.

Technical specifications

Use it with:

Smartphones
 iPod
 iPad
 iPhone
 Tablets
 PC
 MAC
 TV

| | |
|-------------------------|---|
| Amplifier | Class D |
| Output Power | 2 x 50W into 4 Ohms |
| Bluetooth | aptX |
| Voltage | 100 VAC – 240 VAC |
| Inputs | 1 x stereo AUX, Bluetooth, USB, Optical in |
| Outputs | 1 x speaker outputs 1 x output for subwoofer |
| LED | Power & IR indicator & blue Bluetooth |
| Remote control | Power, Mute, Volume up & down, AUX, BT, USB, Optical in, play/pause, next/previous |
| Woofers | 5" 125mm Kevlar™ cone |
| Tweeter | 3/4" soft dome |
| Giftbox includes | 1 MiniPod Active, 1 MiniPod passive, power cord, speaker cable, mini-jack cable, manual, remote, spikes |

Dimensions

| | |
|--------------------|---|
| Width | 210mm |
| Height | 340mm (440mm with spikes) |
| Depth | 200mm |
| Accessories | Wallbracket (aluminum spikes included) |

Wallbracket

User manual / Bedienungsanleitung / Manual del Usuario

PODSPEAKERS
by Scandyna®



Wallbracket for MiniPod

Thank you for purchasing Wallbracket for MiniPod. Please follow the three steps listed in this manual, to ensure a safe installation. The Wallbracket will mount on a solid wall or ceiling, using wood-screws. Never mount your speakers on un-reinforced drywall and always make sure that the Wallbracket is mounted into solid wood, behind the drywall. If you feel unsure about the installation, please contact a qualified installer.

You are responsible for safe mounting of Wallbracket. The use of anchors and screws included in this box, is at the users own risk.

Step 1

Place the wall plate on the mounting surface and use it as a template to mark drilling holes on the surface. Make two holes above the center line and a minimum of one hole below the center line.

Use wood-screws to mount Wallbracket on the surface. When the wall plate has been mounted on the surface, place the wall plate cover over the wall plate.


Step 2

Thread the spine gently, but firmly, through the wall plate until the tapered end is level or horizontal. Fit the bracket base onto the spine and press it until it clicks into the locked position. When in the correct position, the base will be locked and unable to rotate, and the central screw hole will be aligned with the hole in the spine.


Step 3

Remove the rubber feet on the bottom of the MiniPod. While supporting your MiniPod, place it on the Wallbracket base, so that the buds fit into the holes in the bottom. Finish of by tightening the screw with the hexagon key provided.

Wall plate



Wall plate cover



Spine

